

ZEVAC MINI



The same trusted ZEVAC operation, **now faster, lighter, and more versatile than ever before.** Perfect for everything from distribution mains to pigging, ZEVAC MINI brings vent gas recovery to every jobsite.

ZEVAC MINI

48" x 16" x 16" | 185 lbs

Pressure Range: 0 - 150* psig

ZEVAC MINI-HP

48" x 16" x 16" | 285 lbs

Pressure Range: 0 - 1500 psig

ZEVAC MINI		Discharge Pressure, PSIG									
Gas Flow Rate SCFM		150	125	100	75	55	35	25	15	5	0
Drawdown Pressure, PSIG	150	47.1									
	125	38.4	42.1								
	100	29.2	33.0	36.5							
	75	21.0	24.2	26.9	29.1						
	55	14.6	18.0	20.5	22.0	23.4					
	35	9.5	12.2	14.2	15.6	16.4	17.6				
	25	6.7	9.4	11.1	12.5	13.3	13.8	14.2			
	15	3.4	7.0	8.4	9.5	9.9	10.5	10.7	10.9		
	5	2.0	4.6	6.0	6.5	6.9	7.4	7.2	7.3	7.6	
	0	1.0	3.6	4.5	5.5	5.4	5.8	5.9	5.9	6.0	6.0

Stated flow rates based on the following operating conditions:

1. 150 PSI supply air at 375 CFM, chilled.
2. Ambient operating temperature of 75F

* ZEVAC Mini operating pressure is based on a 1:1 supply air ratio, up to the Maximum Allowable Working Pressure (MAWP).

THE PROVEN SOLUTION ANYWHERE VENTING HAPPENS

